

589.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel LGA1200 !



Support:  [Datasheet](#)

- Intel® LGA1200 socket 10/11th Gen Core™ Processors
- 2\* DDR4 2666/2400MHz SO-DIMM up to 64GB
- 3\* USB 3.2 (Type A/Gen2), 1\* USB 3.2 (Type C/Gen1), 4\* USB2.0, 1\* GbE, 1\* COM
- 1\* HDMI1.4, 1\* DP
- DC-19V\_120W Adapter

|               |  |                     |  |
|---------------|--|---------------------|--|
| Dimensions    | – 264 (W) x 199.4 (D) x 38 (H) mm  |                     |  |
| MB model      | – MI09-H470 / Mini ITX (6.7-in * 6.7-in, 170 * 170mm)  |                     |  |
| Part No       | Non-Wifi   | Wifi                |  |
|               | – HBJC511I09-H470-B  | – HBJC511I09-H470-B |  |
| CPU/Chipset   | – Intel® 10/11th LGA 1200 Socket Core i9/i7/i5/i3/Pentium/Celeron Comet Lake-S/Rocket Lake-S Processor (Max:35W)<br>– Intel® H470 chipset<br>Notes: When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.                        |                     |  |
| BIOS          | – AMI SMT Flash ROM  |                     |  |
| Memory        | – 2* DDR4 2666/2400MHz SO-DIMM up to 64GB  |                     |  |
| Network       | – 1* Intel i219V GbE<br>– 1* M.2 E-key Slot 2230 (For WiFi/BT Modul, support CNVi)   |                     |  |
| Storage       | – 1* 2.5" SATA3 6Gb/s internal drive bay<br>– 1* M.2 M-Key (2260/2280, SATA/PCIe)  |                     |  |
| Expansion     | – 1* M.2-2230 E-Key (for WIFI, Optional)   |                     |  |
| Rear I/O Port | – 3* USB 3.2 (Type A/Gen2)<br>– 1* USB 3.2 (Type C/Gen1)<br>– 1* HDMI 1.4 (Max Resolution: 4096x2160@30Hz)<br>– 1* DP (Max Resolution: 4096x2304@60Hz)<br>– 1* RJ45 (Intel i219V GbE)<br>– 1* COM (RS232)<br>– 1* Line-out, 1* Mic-in<br>– 2* Antenna holes (WiFi only)<br>– 1* DC-In Jack |                     |  |

|                   |   |
|-------------------|---|
| Front I/O Port    | <ul style="list-style-type: none"> <li>- 1* Power button, 1* Reset button</li> <li>- 1* Power LED, 1* HDD LED</li> <li>- 1* Line-out, 1* MIC</li> <li>- 4* USB 2.0</li> </ul>             |
| Internal I/O Port | <ul style="list-style-type: none"> <li>- 1* SIM Card holder</li> <li>- 1* M.2-3042 B-Key slot</li> </ul>  |
| Power Source      | <ul style="list-style-type: none"> <li>- AC 90~240V input / DC19V_120W output</li> <li>- MI09 MB : 12~19V DC-in</li> </ul>  |
| Certification     | <ul style="list-style-type: none"> <li>- CE, FCC, RoHS, ErP Ready</li> </ul>  |
| Environment       | <ul style="list-style-type: none"> <li>- Operating Temperature : 0°C~50°C</li> <li>- Storage Temperature : -20°C~70°C</li> <li>- Humidity: 10% ~ 90% RH @40°C (non-condensing)</li> </ul> |
| Packing           | <ul style="list-style-type: none"> <li>- Net Weight■2.4 KG</li> <li>- Gross Weight■3.4 KG</li> <li>- Color Box Dimension■406(W) x 3148(D) x 380(H) mm</li> </ul>                          |